

XD3.6-6kW

Single Phase Hybrid Inverter



- Max. Efficiency 97.5%
- Max. PV Input Voltage 550V
- 150% Peak Output Power
- 2 MPP Trackers, 150% DC Input Oversizing
- Max. PV Input Current 16A, Compatible with High Power Modules

- IP66 Protection Degree: support outdoor installation
- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- DC & AC Type II SPD: prevent lightning damage
- Battery Reverse Connection Protection

- Plug & Play, EPS Switching Under 10ms
- Compatible with Lead-acid and Lithium Batteries
- Max. 6 units Inverters Parallel
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

 Efficient
Higher Revenue

 Intelligent
Simple O&M

 Flexible
Abundant Configuration

 KRAFT
Energy

	XD3K6TL	XD4KTL	XD4K6TL	XD5KTL	XD6KTL
Input (PV)					
Max. PV Input Power	5.4kW	6kW	6.9kW	7.5kW	9kW
Max. PV Input Voltage			550V		
Start-up Voltage			100V		
Rated Voltage	240V	270V	300V	330V	360V
MPPT Voltage Range			100V~550V		
Number of MPP Trackers			2		
Max. PV Input Current			16A		
Output (AC)					
Rated Output Power	3.68kVA	4kVA	4.6kVA	5kVA	6kVA
Max. Output Power	3.68kVA	4.4kVA	4.6kVA	5.5kVA	6.6kVA
Max. Output Current	16A	20A	20.9A	22.7A	30A
Rated Voltage			230V		
Rated Frequency			50Hz / 60Hz		
THDi(@Rated Power)			< 3%		
Power Factor			0.8 leading~0.8 lagging		
Output (EPS)					
Max. Output Power	3.68kVA	4kVA	4.6kVA	5kVA	6kVA
Max. Output Current	16A	20A	20.9A	22.7A	30A
Peak Output Power, Time	5.5kW, 10s	6kW, 10s	6.9kW, 10s	7.5kW, 10s	7.5kW, 10s
Rated Voltage, Frequency			230V, 50Hz		
THDv (@Rated Power)			< 3%		
Switch Time			< 10ms		
Battery					
Battery Type			Lithium, Lead-acid		
Battery Voltage Range			40V-60V		
Max. Charge / Discharge Current			100A		
Communication			CAN		
Efficiency					
Max. Efficiency			97.5%		
EU Efficiency			97.2%		
Battery Charge/Discharge Efficiency			95%		
Protection					
DC Reverse Polarity Protection / Insulation Resistance Monitoring / Ground Fault Monitoring				Yes	
Over Current / Over Voltage Protection				Yes	
Battery Soft Start Protection				Yes	
AFCI Protection				Optional	
Surge Protection				Type II	
Communication					
Display			LCD		
Communication			RS485 / CAN / WIFI / 4G / LAN / Bluetooth		
General Data					
Dimension (W*H*D)			490 x 395 x 200 mm		
Weight			15kg		
Operating Temperature Range			-30°C~ +60°C		
Cooling Method			Natural		
Protection Degree			IP66		
Max. Operating Altitude			4000 m		
Noise			≤ 25dB		
Relative Humidity			0~100%		
Self-consumption			< 10W		
Topology			High Frequency Isolation (For battery)		